

No.SDHL250601045901FT

Page 1 of 5

Date: Jul 16, 2025

FOSHAN OFIEXPERTS FURNITURE CO.,LTD 3RD FLOOR, BUILDING 2, NO. 16 YUANNAN 2ND ROAD, SHAZUI SECTION, JIUJIANG INDUSTRIAL PARK, NANHAI DISTRICT, FOSHAN, GUANGDONG, CHINA.

Sample Description : OFFICE CHAIR

Item No. : MC07-AS(BUTTON)

Manufacturer : FOSHAN OFIEXPERTS FURNITURE CO.,LTD

: Jun 19, 2025

As above test item and its relevant information regarding to the submission are provided and confirmed by the applicant. SGS is not liable to either the test item or its relevant information, in terms of the accuracy, suitability,

reliability or/and integrity accordingly.

Sample Receiving Date

Test Performing Date : Jun 19, 2025 to Jul 16, 2025

Test Performed : Selected test(s) as requested by applicant

Test Result Summary

No.	Test(s) Requested	Result(s)	Comments	
1	Clause 5, 7, 10, 11.3.1, 11.4, 12, 13, 14 and 15 of ANSI/BIFMA X5.1-2017 (R2022)	PASS	1	
For further details, please refer to the following page(s)				

Signed for and on behalf of SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch

Mars Leury

Marco Leung Authorized Signatory





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's sindings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction force were cising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: Ch.Doccheck@ags.com"

1-2/F., Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Dalliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757)22805888 www.sgsgroup.com.cn 中国·广东·佛山市顺德区大良街道办事处五沙社区居民委员会顺和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757)22805888 sgs.china@sgs.com



No.SDHL250601045901FT

Page 2 of 5

TESTS AND RESULTS

Date: Jul 16, 2025

Test Conducted:

Clause 5, 7, 10, 11.3.1, 11.4, 12, 13, 14 and 15 of ANSI/BIFMA X5.1-2017 (R2022) General-Purpose Office Chairs.

No. of Sample:

4 pieces. For more sample information and pictures, please refer to the following page.

Chair Type:

☐ Type I. Tilting chair
☐ Type II. Fixed seat angle, tilting backrest
☐ Type III. Fixed seat angle, fixed backrest

Force: 667 N (150 lbf.) for one minute. Acceptance level: There shall be no loss of serviceability to the chair. Proof Load Force: 1001 N (225 lbf.) for one minute. Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	Test and Requirements	Test Results			
Functional Load Force: 667 N (150 lbf.) for one minute. Acceptance level: There shall be no loss of serviceability to the chair. Proof Load Force: 1001 N (225 lbf.) for one minute. Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	·				
Acceptance level: There shall be no loss of serviceability to the chair. Proof Load Force: 1001 N (225 lbf.) for one minute. Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rass PASS PASS Rase: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	Functional Load				
Proof Load Force: 1001 N (225 lbf.) for one minute. Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	Force: 667 N (150 lbf.) for one minute.	PASS			
Force: 1001 N (225 lbf.) for one minute. Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	Acceptance level: There shall be no loss of serviceability to the chair.				
Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	Proof Load				
Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	Force: 1001 N (225 lbf.) for one minute.	PASS			
7 Drop Test – Dynamic Functional Load Test A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	Acceptance level: There shall be no sudden and major change in the structural integrity				
A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 PASS Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	of the chair. Loss of serviceability is acceptable.				
A test bag weighting 102 kg (225 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 PASS Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.	7 Drop Test – Dynamic				
uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 PASS PASS PASS					
features, tested both in highest and lowest position). Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Acceptance level: There shall be no loss of serviceability. Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.		PASS			
Proof Load Test A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
A test bag weighting 136 kg (300 lb.) shall be raised 152 mm (6 in.) above the uncompressed seat and released one time (For chairs with seat height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
uncompressed seaf and released one time (For chairs with seaf height adjustment features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.		PASS			
features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
features, tested both in highest and lowest position). Acceptance level: There shall be no sudden and major change in the structural integrity of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
of the chair. Loss of serviceability is acceptable. 10 Seating Durability Tests – Cyclic 10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
10.3 Impact Test Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Drop weight: 57 kg (125 lb.) Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Drop height: 36 mm (1.4 in.) above the uncompressed surface on the seat Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 PASS Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.		PASS			
Cycles: 100,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Acceptance level: There shall be no loss of serviceability to the chair. 10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 PASS Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
10.4 Front Corner Load-Ease Test – Cyclic – Off-center Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Force: 890 N (200 lbf.) Cycles: 40,000 Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Cycles: 40,000 PASS Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.					
Rate: Between 10 and 30 cycles per minute. Acceptance level: There shall be no loss of serviceability to the chair.		PASS			
Acceptance level: There shall be no loss of serviceability to the chair.					
	Acceptance level: I nere shall be no loss of serviceability to the chair. 11 Stability Tests				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction force were reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ags.com



Test Report No.SDHL250601045901FT Date: Jul 16, 2025 Page 3 of 5

Test and Requirements	Test Results		
11.3.1 Rear Stability Test for Type III Chairs			
Load the chair with 6 disks.			
• F = 0.1964 (1195 – H) Newton. H is the seat height in mm.			
• [F = 1.1 (47 – H) pounds force.]. H is the seat height in inches.	PASS		
For chairs with seat height equal to or greater than 710 mm (28.0 in.), a fixed force of 93			
N (20.9 lbf.) shall be applied.			
Acceptance level: The chair shall not tip over.			
11.4 Front Stability			
Load 61 kg (135 lb.) on 60 mm (2.4 in.) from the front center edge and a horizontal	PASS		
outward force of 20 N (4.5 lbf.) applied.			
Acceptance level: The chair shall not tip over as the result of the force application.			
12 Arm Strength Test - Vertical – Static			
Functional Load			
Force: 750 N (169 lbf.) for one minute.	DACC		
Acceptance level: There shall be no loss of serviceability. For a height adjustable arm,	PASS		
failure to hold its height adjustment position to within 6 mm (0.25 in.) from its original set			
position as the result of the loading is considered a loss of serviceability. Proof Load			
Force: 1125 N (253 lbf.) for 15 seconds.			
Acceptance level: There shall be no sudden and major change in the structural integrity	PASS		
of the chair. For a height adjustable arm, a sudden drop in height of greater than 25 mm	17400		
(1 in.) does not meet this requirement. Loss of serviceability is acceptable.			
13 Arm Strength Test - Horizontal – Static			
Functional Load			
Force: 445 N (100 lbf.) for one minute in the outward direction.	PASS		
Acceptance level: A functional load applied once shall cause no loss of serviceability.			
Proof Load			
Force: 667 N (150 lbf.) for 15 seconds in the outward direction.	DACC		
Acceptance level: A proof load applied once shall cause no sudden and major change in	PASS		
the structural integrity of the unit. Loss of serviceability is acceptable.			
14 Backrest Durability Test - Cyclic - Type I			
Weight on seat: 109 kg (240 lbs.)			
Load on backrest: 445 N (100 lbf.)	PASS		
Cycles: 120,000	17.00		
Rate: Between 10 and 30 cycles per minute.			
Acceptance level: There shall be no loss of serviceability.			
15 Backrest Durability Test - Cyclic - Type II and III			
Weight on seat: 109 kg (240 lbs.)			
Load on backrest: 334 N (75 lbf.)	PASS		
Cycles: 120,000			
Rate: Between 10 and 30 cycles per minute.			
Acceptance level: There shall be no loss of serviceability.			

Remark:

1. For the sample information and pictures, please refer to the following page.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction force were reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ags.com

or email: CN.Doccheck@sgs.com 1-2/F., Building 1, European Industrial Park, No.1, Shunhe South Road, Wusha, Daliang, Shunde District, Foshan, Guangdong, China 528300 t (86-757)22805888 www.sgsgroup.com.cn 中国・广东・佛山市順徳区大良街道办事处五沙社区居民委員会順和南路1号欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757)22805888 sgs.china@sgs.com



No.SDHL250601045901FT

Date: Jul 16, 2025

Page 4 of 5

SAMPLE INFORMATION AND PICTURES

Weight: 16.2 kg

Overall Dimensions: 700 mm D x 897 mm W x (1070~1225) mm H

Other Dimensions: Base radius 350 mm

Sample as Received











Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction force were reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ags.com

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@egs.com

1-2/F, Building I, European Industrial Park, No. I, Shumhe South Road, Wusha, Dallang, Shunde District, Foshan, Guangdong, China 528300 t (86-757) 22805888 www.sgsgroup.com.cn
中国・广东・佛山市順德区大良街道办事处五沙社区民委员会顺和南路马欧洲工业园一号厂房首层、二层 邮编: 528300 t (86-757) 22805888 sgs.china@sgs.com



No.SDHL250601045901FT

Date: Jul 16, 2025

Page 5 of 5



Unless otherwise stated, the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule (w=0) stated in ILAC-G8:09/2019.

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction force were reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ags.com